

D7615PDTX

Full HD Capacitive Desktop Conference Terminal



Description

The device is designed with the industry-leading desktop architecture using integrated screen and host, and aluminum alloy ultra-narrow bezel. It is equipped with a 15.6" multi-touch high-resolution IPS display, and a 10.1" LCD name display on the other side to display name information, with a clear and bright display effect. It features a capacitive touch screen, so you can call the system office software for ink writing, and save the original handwriting of the original document when writing comments on the screen. It adopts pure network architecture with simple system wiring and easy commissioning and maintenance. It offers low power consumption, low heat generation and good heat dissipation, exquisite in surface treatment process, with an optimal balance between aesthetics and tactile experience.

Features

- Intel Core i5 6th Generation 6 (Performance will continue to be optimized as the product is upgraded).
- RAM: 8GB.
- Hard drive capacity: 128GB SSD.
- NIC: 1×Gigabit NIC, RJ45 connector.
- Standard interface: 2×USB (3.0/2.0), 1×DC port.
- Operating environment: Environment temperature: -10°C~50°C; relative humidity: 0%~95%, no condensation.
- Operating power: DC 17V/6.5A 120W.

Microphone functions:

- Electret cardioid condenser microphone.
- With a high-density 5-pin aviation connector.

- With work indicator light ring.
- In compliance with IEC60914 international standard.
- Speaker-only conference unit.
- Electret cardioid condenser pickup, red for speaking.
- With a knob-type microphone rod, mini microphone, available in black and silver.
- The microphone stem can be manually adjusted for the desired angle, enabling convenient speaking.
- It features an internal magnetic hi-fi speaker that automatically mutes when the microphone is turned on, making it difficult to make a whistle.
- With super strong anti-interference ability of mobile phones.
- It holds a microphone on/off button and the chairman unit has a chairman priority button.
- Each conference unit has a unique ID number.
- In conjunction with the camera, it can realize automatic camera tracking after setting via the conference control host or PC control software.
- In conjunction with the control host, the unit has a self-test function. The items to be tested are: buttons, microphone, LED indicators.
- The unit is a passive device, powered by the system host.
- With automatic equalization, it can suppress whistling. When the microphone is on, the local speaker will be automatically turned off to prevent sound feedback.
- Support “hand-in-hand” or “T-type” and “+type” connection mode.
- Through the host settings, the chairman unit has a priority function (to mute or turn off all delegate units) and a podium mode (the chairman unit is always on).
- The chairman unit has the function of approving applications for speaking from the delegates.
- The chairman unit is not limited by the number of speakers and can be opened freely.
- The chairman unit has the priority function of having full control over the order of the meeting.
- There is no restriction on the connection position of the chairman unit.

Specifications

Model	D7615PDTX
CPU	Intel Core i5 6th Generation
RAM	8GB
Hard Drive	128GB SSD
NIC	1×Gigabit NIC, RJ45 connector
Standard Interface	2×USB (3.0/2.0), 1×DC port
Operating Temperature	-10°C~50°C
Operating Humidity	0%~95%, no condensation
Operating Power	DC 17V/6.5A 120W