

## D7734

## All-Weather Passive Line Array Full-Range Loudspeaker



## Description

The D7734 All-Weather Passive Line Array Full-Range Loudspeaker features a three-way configuration with dual 12-inch low-frequency drivers, dual 3.5-inch mid-frequency drivers, and dual 1.75-inch high-frequency drivers. It delivers powerful, high-fidelity sound with strong projection and exceptional clarity. With its robust enclosure and IP66-rated all-weather design, it ensures reliable performance in a wide range of indoor and outdoor applications.

## Features

- Enclosure molded from polymer composite materials, with a five-layer waterproof and dustproof grille.
- External crossover with three-way design, delivering clear and delicate sound with strong penetration.
- All-weather design meeting IP66 protection rating.
- Three-point suspension mounting for easy installation.

## Specifications

Model	D7734
System Configuration	2×12" LF, 2×3.5" MF, 2×1.75" HF
Frequency Response ( $\pm 3\text{dB}$ )	LF: 60Hz-1kHz, MF+HF: 500Hz-18kHz
Crossover Point	600Hz
Sensitivity	LF: 101 $\pm$ 2dB, MF+HF: 110 $\pm$ 2dB
MAX. SPL.	LF: 130 $\pm$ 2dB, MF+HF: 134 $\pm$ 2dB
Input Impedance	LF: 8Ω, MF+HF: 16Ω
Rated Power	LF: 800W, MF+HF: 300W
Directivity (H)	90°
Dimensions (H×W×D)	374×756×550mm
Weight	39kg