

# D8115TZ

## Display Retractable Monitor Motorized Dual-screen Lift with Backside Screen



### Description

D8115TZ with embedded architecture, according to the needs of different meetings, the LCD screen lift one terminal for individual control, network control settings; integrated design, using aluminum alloy structure, the overall exquisite equipment, lightweight, beautiful, atmospheric.

### Features

- Ultra-thin double-sided terminal with motorized lifter;
- 15.6" IPS touch main screen with a resolution of 1920\*1080;
- 7" LCD electronic nameplate sub screen, resolution 1024\*600;
- Ultra-narrow bezel design with rounded edge;
- Aluminum alloy case and sandblasted anodized surface;
- Support full-screen touch, slide, drag, zoom to view conference data;
- Embedded motorized lifting system, and can touch the button to control;
- Monitor adjustable angle: 0-30°;
- Low power consumption, great heat dissipation, support for power-saving mode such as standby and hibernation;
- Ultra-silent motor, and the parts used in accordance with ISO 9001 quality standards, can operate stably and quietly;
- Support RS232/RS485 background centralized control.

## Specifications

Model	D8115TZ
Screen	Main screen (15.6", 16:9), sub screen (7", 16:9)
Screen resolution	Main screen 1920*1080, sub screen 1024*600
Interface resolution	1920*1080
Panel dimension	470*80*5
Case dimension	450*68*660
Angle	0-30° adjustable
Backlight/contrast/brightness	LED/800: 1/220
Touch points	10
Touch technology/Surface hardness	7 (Mohs hardness scale)
Operating system	Windows7
CPU	I3 2.30Hz
RAM	DDR 4G
Hard disk	64G (SSD)
Basic interface	COM*2, USB*1, Switch*1, RJ45*1
Power	AC220V 50/60HZ
Power supply	100W
Installation	Desktop embedded
Material	Anodized metal SGCC
Working temperature	-5~45 °C
Working humidity	10%~95%
Storage temperature	-25~65 °C