

DP-X8E

LED Video Controller



Description

DP-X8E is a controller possessing powerful video signal input and processing capacity. It supports 4K inputs with DP 1.4 and HDMI 2.0 connectors, and 2K inputs with HDMI 1.4 and DVI connectors, and the multiple signals can be seamlessly switched. Equipped with 8 Gigabit Ethernet ports, the controller can greatly meet your different demands. Additionally, it boasts abundant practical functions that enable flexible screen control and high-quality image display.

Features

- Input connectors: 1×DP 1.4, 1×HDMI 2.0, 2×HDMI 1.4, 2×DVI.
- Input resolution: up to 4096×2160@60Hz, supporting customized setting.
- Output connectors: 8×Gigabit Ethernet port.
- Support video source switching, cropping, splicing and scaling.
- Support up to 6 windows, of which the location and size can be freely adjusted.
- Support precise color management and display gamut adjustment.
- Support video sync.
- Separate audio input and output.
- Support RS232 control.
- Support LAN control.
- Support HDCP.
- Support brightness and color temperature adjustment.
- Support better gray at low brightness.

Specifications

Model		DP-X8E
Size		2U
Electrical Specifications	Input Voltage	AC100~240V, 50/60Hz
	Power Consumption	50W
Operating Environment	Temperature	-20°C~70°C/-4°F~158°F
	Humidity	0%RH~80%RH, non-condensing
Storage Environment	Temperature	-30°C~80°C/-22°F~176°F
	Humidity	0%RH~90%RH, non-condensing
Device Specifications	Dimensions	W×H×L/482.6mm×88.0mm×414.1mm/19"×3.5"×16.3"
	Net Weight	4.8kg/10.58lbs
Packing Specifications	Dimensions	W×H×L/525.0×150.0×495.0mm3/20.7"×5.9"×19.5"
	Net Weight	1.8kg/3.97lbs

Technical Parameters

HDMI 2.0(A)

Standard	HDMI 2.0 specification, EIA/CEA-861 standard		
	Backward compatible with HDMI 1.4 and HDMI 1.3		
Input	Format	Maximum Input Resolution	
	8bit	RGB444	4096×2160@60Hz
		YCbCr444	
		YCbCr422	
Frame Rate	23.98/24/25/29.97/30/50/59.97/60/120/144Hz		
Support audio input			

DP 1.4

Standard	DP 1.4 specification, support EDID		
Input	Format	Maximum Input Resolution	
	8bit	RGB444	4096×2160@60Hz
		YCbCr444	
		YCbCr422	
Frame Rate	23.98/24/25/29.97/30/50/59.97/60/120/144Hz		
Support audio input			

HDMI 1.4

Standard	HDMI 1.4 specification, HDCP1.4 compliant		
Input	Format	Maximum Input Resolution	
	8bit	RGB444	1920×1200@60Hz
		YCbCr444	
		YCbCr422	
Frame Rate	23.98/24/25/29.97/30/50/59.97/60Hz		
Support audio input			

DVI

Standard	Support HDCP		
Input	Format	Maximum Input Resolution	
	8bit	RGB444	1920×1200@60Hz
		YCbCr444	
		YCbCr422	
Frame Rate	23.98/24/25/29.97/30/50/59.97/60Hz		

Front Panel



Item	Function
LCD	Display the operation menu and system information
Knob	Turn the knob to select an item or adjust the parameter; press the knob to confirm your selection or adjustment
Function Keys	OK: Enter key Bright: Brightness adjustment ESC: Exit the current menu or operation Black: Blackout Lock: Lock all the keys of the front panel Freeze: Freeze the image
Mode Keys	HDMI1/DP/HDMI2/HDMI3/DVI1/DVI2: Video source selection keys, which function as number selection keys in mode selection Signal: View the signals Mode: Output mode selection
Power Switch	Switch the device on or off

Rear Panel



Input	
HDMI 2.0	1×HDMI 2.0
DP 1.4	1×DP 1.4
HDMI1, HDMI2	2×HDMI 1.4
DVI1, DVI2	2×DVI
Output	
Port 1-8	RJ45, 8×Gigabit Ethernet ports
Control	
LAN	Network control (communication with PC, or access network)

RS232	RJ11(6P6C)*, connect to the third party device
USB OUT	USB output, for cascading with the controller
USB IN	USB input, connecting to PC for debugging
Audio	
AUDIO IN	Audio input, for inputting audio signals from the computer or other devices
AUDIO OUT	Audio output, for outputting audio signals to the speaker (Support outputting the audio signals of HDMI and DP)
Power	
Mains Input	AC 100~240V , AC power connector, containing a built-in fuse

* DB9 female to RJ11(6P6C) cable:

