

## DSP7910

### 250W Professional Conference Speaker



## Description

The product adopts a phase-inverted bass-reflex two-way speaker system. Its wooden enclosure is coated with black speckled water-based paint, and acoustic sound-transmitting cotton is attached to the back of the metal mesh. This professional conference speaker is well-suited for a wide range of scenarios, including corporate meeting rooms, lecture halls, and multi-functional venues.

## Features

- Phase-inverted bass-reflex two-way speaker system.
- The wooden speaker enclosure is coated with black speckled water-based paint, with acoustic sound-penetrating cotton attached to the back of the metal mesh.
- The top of the speaker is equipped with a hanging hole, which can be vertically hung and installed by using a ring and rope accessories on the back hanging hole.
- There are two hanging holes on the back and side of the speaker, which can be installed by D3A bracket wall.

- The speaker is equipped with a slot at the bottom, which can be installed on the wall with D5A bracket or on the floor with D6A tripod.

## Specifications

Model	DSP7910
System Composition	10" woofer x 1, 1.35" tweeter x 1
Frequency Response (±3dB)	55Hz-18,000Hz
Sensitivity	96±2dB
Max. SPL	119±2dB
Input Impedance	8 Ω
Rated Power	250W
Directivity (H×V)	90°×45°
Dimension (H×W×D)	515×307×330mm
Weight	14.0kg

## Product Information

