

DSP7912

350W Professional Conference Speaker



Description

The product adopts a phase-inverted bass-reflex two-way speaker system. Its wooden enclosure is coated with black speckled water-based paint, and acoustic sound-transmitting cotton is attached to the back of the metal mesh. This professional conference speaker is well-suited for a wide range of scenarios, including corporate meeting rooms, lecture halls, and multi-functional venues.

Features

- Phase-inverted bass-reflex two-way speaker system.
- The wooden speaker enclosure is coated with black speckled water-based paint, with acoustic sound-penetrating cotton attached to the back of the metal mesh.
- The top of the speaker is equipped with a hanging hole, which can be vertically hung and installed by using a ring and rope accessories on the back hanging hole.
- The speaker is equipped with a slot at the bottom, which can be installed on the wall with D5A bracket or on the floor with D6A tripod.

Model	DSP7912
System Composition	12" woofer x 1, 1.75" tweeter x 1
Frequency Response ($\pm 3\text{dB}$)	55Hz-18,000Hz
Sensitivity	98 $\pm 2\text{dB}$
Max. SPL	123 $\pm 2\text{dB}$
Input Impedance	8 Ω
Rated Power	350W
Directivity (H \times V)	90 $^\circ$ \times 50 $^\circ$
Dimension (H \times W \times D)	600 \times 386 \times 415mm
Weight	22.0kg

Product Information

