

DT4600

Networked Dante Desktop Gooseneck Microphone



Description

Featuring Dante-enabled IP audio networking, this gooseneck conference microphone base is equipped with a tact switch and a clear status indicator. Built with a heavy-duty die-cast body and acoustic vibration-isolation rubber feet, it effectively minimizes structure-borne noise caused by desktop impacts. Delivering clean, pristine voice capture and network flexibility, it is tailored for modern boardrooms, distance learning, and high-demand sound environments.

Features

- Connects directly to the network via an Ethernet cable or integrates quickly into an existing network through a switch, eliminating the need for additional audio cables or soldering..
- Integrates user logic control, allowing local control of talk/mute functions and remote operation of Dante devices in remote mode.
- The Dante microphone is powered via PoE from the network switch, enabling a scalable Dante audio system.
- Features a soft-touch microphone button to eliminate mechanical noise when switching the microphone on or off.
- Provides strong resistance against mobile phone interference, electromagnetic interference, and high-frequency interference.

Specifications

Model	DT4600
Transducer Type	Condenser
Polar Pattern	Hypercardioid
Frequency Response	20Hz-20kHz
Dynamic Range	85dB
SNR	72dB
Power Supply	PoE IEEE802.3af Standard
Dante Output Connector	RJ45 (Use a shielded Cat5 or Cat6 Ethernet cable for connection)
Gooseneck Length	350mm
Microphone Base Dimensions	135mm×95mm×45mm
Weight	1.22kg